



## Technical Data Sheet



### SYNTHETIC COMPRESSOR CLEANER COMP CLEAN II ®

**CPI COMP CLEAN II®** is a synthetic fluid formulated in order to dissolve and remove sludge and residuals due to the mineral oil oxidation (naphthenic, paraffinic, and hydrogenated) into the air compressors.

#### Benefits

- Formulated with an innovative **molecularly modified synthetic base**
- Chemically stable and inert
- Toxicologically safe
- Strong-fading additive
- Compatibility with building materials
- Fast demulsibility

#### Applications

**CPI COMP CLEAN II®** is recommended for the cleaning operations of the air compressors until a maximum of 400 hours.

#### Performance Data

Properties	Reference method	Typical values
Colour	ASTM D1500	0.5
Flammability, COC, °C	ASTM D0092	229
Viscosity, cSt at 40°C	ASTM D0445	38.9
Viscosity, cSt at 100°C	ASTM D0445	5.5
Flow, °C	ASTM D0097	- 45
Mechanical emulsion, 54°C, mL water, (min.)	ASTM D1401	40 (5)
Density	ASTM D1298	.965

#### Vuoto Service Srl

##### Headquarters

Via Filippo Meda, 16  
20037 Paderno Dugnano (MI)

##### Branch

Zona Industriale  
67062 Magliano de' Marsi (AQ)

Tel. (0039) 02.99044533 – Fax (0039) 02.9105503

E-mail: [info@vuotoservice.net](mailto:info@vuotoservice.net)

Website: [www.vuotoservice.net](http://www.vuotoservice.net)