

CP-4600-F Series Lubricants

CP-4600-F Series lubricants are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon fluids. Primary benefits include:

- Extended 4,000 hour typical life
- Improved lubrication at high and low temperatures
- Reduced volatility
- Compatible with mineral oils
- Superior corrosion protection

These high-performance lubricants are recommended for use in flooded rotary screw compressors.

For CP-4600-F Series lubricants approved for federally inspected food processing facilities (H1) – consult your CPI representative. Your local CPI representative can help you determine the appropriate product and viscosity for your needs.



All CPI lubricants are Kosher, Pareve, and Halal registered.

Preliminary Product Selection Guide

Product Name	Viscosity*				Viscosity Index ASTM D2270
	@ 40° C cSt ASTM D445	@ 100° C cSt ASTM D445	@ 100° F SUS	@ 210° F SUS	
CP-4600-5-F	5.10	1.70	44.0	31.9	122
CP-4600-15-F	16.8	3.80	90.8	39.1	117
CP-4600-32-F	31.4	6.00	162	46.3	140
CP-4600-46-F	46.9	7.90	241	52.7	139
CP-4600-68-F	68.5	10.4	353	61.6	139
CP-4600-100-F	96.8	14.0	500	75.0	148
CP-4600-150-F	150	19.9	778	100	153
CP-4600-220-F	217	24.4	1134	121	141
CP-4600-320-F	320	33.0	1678	161	145
CP-4600-460-F	443	46.0	2320	222	161

* These values are not intended for use in preparing specifications. For assistance, consult your CPI representative.



North America

2300 James Savage Road
Midland, MI 48642
Telephone: 989 496-3780
Fax: 989 496-2313

Europe

Belasis Business Centre
Greenwood Road
Stockton-on-Tees
TS23 4EA, UK
Telephone: 44 1642 565266
Fax: 44 1642 566224

Asia

27F, Majesty Building
138 Pu Dong Avenue
Pu Dong New District
Shanghai, China 200120
Telephone: 86 21 3866 0568
Fax: 86 21 5887 6939

Asia

44 Tanjong Penjuru
Singapore 609032
Telephone: 65 62641644
Fax: 65 62642105

www.cpieng.com
For general inquiries:
sales@cpieng.com