

Sabroe PAO68

Synthetic Refrigeration Oil

Product Description

Sabroe PAO68 Synthetic Refrigeration Oil is a fully synthetic lubricant formulated using wax free, synthesized hydrocarbons of polyalphaolefin (PAO) which have demonstrated outstanding resistance to thermal/oxidative degradation. Even in the worst operating conditions this oil will reduce sludge and deposit formation and is remarkable for a very low oil carryover. This oil is miscible with most conventional mineral refrigeration oils. This may however detract from the outstanding performance properties.

Features and Benefits

Superior thermal stability	Long oil life, extended drain intervals, less maintenance costs
Low carry-over	Improves evaporator efficiency
Wax free	Excellent low temperature fluidity, no wax deposits
Very low pour point	Enables lower evaporating temperatures, easier oil drainage
Low volatility	Reduced need of oil top-up, avoids viscosity build-up

Applications

Sabroe PAO68 Synthetic Refrigeration Oil is particularly suited for use in ammonia compressors with high operating temperatures and/or systems with very low evaporative temperatures.

Sabroe PAO68 is Food Grade registered by NSF International with Category Code H1.

Sabroe PAO68 is also suitable for certain HCFC (R22) applications taking the drop of viscosity into account.

Typical Properties

Test Procedure	Typical	Test Method
Viscosity @ 40°C, cSt	66	ASTM D445
Viscosity @ 100°C, cSt	10	ASTM D445
Viscosity Index	138	ASTM D2270
Specific Gravity, g/ml	0.83	ASTM D4052
Pour Point, °C	<-50	ASTM D97
Flash Point, °C	266	ASTM D92
Acid no., mg KOH/g	0.03	ASTM D974

Johnson Controls Denmark

www.johnsoncontrols.com

www.sabroe.com

