

CP-1507-150

PRODUCT DESCRIPTION

CP-1507-150 product is polyalkylene glycol lubricants, formulated to give negligible solubility or dilution in contact with hydrocarbon liquids or vapors. The ability of these lubricants to withstand dilution by hydrocarbon gases is particularly advantageous in liquid ring vacuum pump and centrifugal compressors handling high concentrations of hydrocarbon and gasoline vapors.

CP-1507-150 is a heat stable polymer in the absence of oxygen. They are soluble in water.

TYPICAL PROPERTIES*

CP-1507-150

Viscosity@40°C, cSt, ASTM D445	115.10
Viscosity@100°C, cSt	17.61
Viscosity@100°F, SUS	587
Viscosity@210°F, SUS	90.5
Viscosity Index ASTM D2270	159
Density, lb/gal, 60°F	9.27
Density, lb/gal 100°F(40°C)	1.140
Density, lb/gal 150°F(66°C)	1.120
Density, lb/gal 200°F(93°C)	1.110
Pour Point °F(°C)ASTM D97	22(-5.6)
Flash Point, C.O.C., °F(°C)ASTM D92	495(257)
Fire Point, C.O.C., °F(°C)ASTM D92	540(282)
Specific Gravity, ASTM D1298	1.11

**These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com